



US009104670B2

(12) **United States Patent**  
**Wadycki et al.**

(10) **Patent No.:** **US 9,104,670 B2**  
(45) **Date of Patent:** **Aug. 11, 2015**

(54) **CUSTOMIZED SEARCH OR ACQUISITION  
OF DIGITAL MEDIA ASSETS**

(75) Inventors: **Andrew Wadycki**, Santa Clara, CA  
(US); **Jason Douglas**, Sunnyvale, CA  
(US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 646 days.

5,479,488 A	12/1995	Lennig et al.
5,577,241 A	11/1996	Spencer
5,608,624 A	3/1997	Luciw
5,682,539 A	10/1997	Conrad et al.
5,727,950 A	3/1998	Cook et al.
5,748,974 A	5/1998	Johnson
5,794,050 A	8/1998	Dahlgren et al.
5,826,261 A	10/1998	Spencer
5,895,466 A	4/1999	Goldberg et al.
5,899,972 A	5/1999	Miyazawa et al.
5,915,249 A	6/1999	Spencer

(Continued)

#### FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **12/841,075**

EP	1245023 (A1)	10/2002
JP	06 019965	1/1994

(22) Filed: **Jul. 21, 2010**

(Continued)

(65) **Prior Publication Data**

US 2012/0023095 A1 Jan. 26, 2012

#### OTHER PUBLICATIONS

Alfred App, 2011, <http://www.alfredapp.com/>, 5 pages.

(Continued)

(51) **Int. Cl.**  
**G06F 17/30** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **G06F 17/30017** (2013.01); **G06F 17/3053**  
(2013.01)

Primary Examiner — Thanh-Ha Dang

(74) Attorney, Agent, or Firm — Kilpatrick Townsend &  
Stockton LLP

(58) **Field of Classification Search**

CPC ..... G06F 17/30781; G06F 17/3005; G06F  
17/30064; G06F 17/30699; G06F 17/30837;  
G06F 17/30017; G06F 17/3053; G06F  
17/3082; G06F 17/30112  
USPC ..... 707/723, 913  
See application file for complete search history.

(57)

#### ABSTRACT


Improved techniques for using usage data are disclosed. The usage data can pertain to a user of an electronic device. The usage data can be monitored and recorded on the electronic device. The improved techniques are particularly useful when the electronic device is a mobile electronic device. In one embodiment, the usage data can be used to enhance searching of digital assets, such as digital media assets, resident at a local or remote repository. In another embodiment, the usage data can be used to determine content to be resident locally on the electronic device. In still another embodiment, the usage data can be used to present (e.g., display) information on the electronic device.

(56) **References Cited**

#### U.S. PATENT DOCUMENTS

4,974,191 A	11/1990	Amirghodsi et al.
5,128,672 A	7/1992	Kaehler
5,282,265 A	1/1994	Rohra Suda et al.
5,386,556 A	1/1995	Hedin et al.
5,434,777 A	7/1995	Luciw

**21 Claims, 11 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,987,404	A	11/1999	Della Pietra et al.	7,454,351	B2	11/2008	Jeschke et al.
6,052,656	A	4/2000	Suda et al.	7,475,010	B2	1/2009	Chao
6,081,750	A	6/2000	Hoffberg et al.	7,483,894	B2 *	1/2009	Cao ..... 1/1
6,088,731	A	7/2000	Kiraly et al.	7,502,738	B2	3/2009	Kennewick et al.
6,144,938	A	11/2000	Surace et al.	7,526,466	B2	4/2009	Au
6,188,999	B1	2/2001	Moody	7,539,656	B2	5/2009	Fratkina et al.
6,233,559	B1	5/2001	Balakrishnan	7,546,382	B2	6/2009	Healey et al.
6,334,103	B1	12/2001	Surace et al.	7,548,895	B2	6/2009	Pulsipher
6,421,672	B1	7/2002	McAllister et al.	7,555,431	B2	6/2009	Bennett
6,434,524	B1	8/2002	Weber	7,565,363	B2 *	7/2009	Anwar ..... 1/1
6,446,076	B1	9/2002	Burkey et al.	7,599,918	B2	10/2009	Shen et al.
6,453,292	B2	9/2002	Ramaswamy et al.	7,620,549	B2	11/2009	Di Cristo et al.
6,499,013	B1	12/2002	Weber	7,624,007	B2	11/2009	Bennett
6,501,937	B1	12/2002	Ho et al.	7,634,409	B2	12/2009	Kennewick et al.
6,513,063	B1	1/2003	Julia et al.	7,640,160	B2	12/2009	Di Cristo et al.
6,523,061	B1	2/2003	Halverson et al.	7,647,225	B2	1/2010	Bennett et al.
6,526,395	B1	2/2003	Morris	7,657,424	B2	2/2010	Bennett
6,532,444	B1	3/2003	Weber	7,672,841	B2	3/2010	Bennett
6,598,039	B1	7/2003	Livowsky	7,684,985	B2	3/2010	Dominach et al.
6,601,026	B2	7/2003	Appelt et al.	7,693,720	B2	4/2010	Kennewick et al.
6,615,172	B1	9/2003	Bennett et al.	7,698,131	B2	4/2010	Bennett
6,633,846	B1	10/2003	Bennett et al.	7,702,500	B2	4/2010	Blaedow
6,650,735	B2	11/2003	Burton et al.	7,702,508	B2	4/2010	Bennett
6,665,640	B1	12/2003	Bennett et al.	7,707,027	B2	4/2010	Balchandran et al.
6,691,111	B2	2/2004	Lazaridis et al.	7,707,267	B2	4/2010	Lisitsa et al.
6,691,151	B1	2/2004	Cheyser et al.	7,711,672	B2	5/2010	Au
6,735,632	B1	5/2004	Kiraly et al.	7,716,056	B2	5/2010	Weng et al.
6,742,021	B1	5/2004	Halverson et al.	7,720,674	B2	5/2010	Kaiser et al.
6,757,362	B1	6/2004	Cooper et al.	7,725,307	B2	5/2010	Bennett
6,757,718	B1	6/2004	Halverson et al.	7,725,320	B2	5/2010	Bennett
6,778,951	B1	8/2004	Contractor	7,725,321	B2	5/2010	Bennett
6,792,082	B1	9/2004	Levine	7,729,904	B2	6/2010	Bennett
6,807,574	B1	10/2004	Partovi et al.	7,729,916	B2	6/2010	Coffman et al.
6,842,767	B1	1/2005	Partovi et al.	7,734,461	B2	6/2010	Kwak et al.
6,851,115	B1	2/2005	Cheyser et al.	7,752,152	B2	7/2010	Paek et al.
6,859,931	B1	2/2005	Cheyser et al.	7,783,486	B2	8/2010	Rosser et al.
6,895,380	B2	5/2005	Sepe, Jr.	7,809,570	B2	10/2010	Kennewick et al.
6,895,558	B1	5/2005	Loveland	7,818,176	B2	10/2010	Freeman et al.
6,928,614	B1	8/2005	Everhart	7,822,608	B2	10/2010	Cross, Jr. et al.
6,937,975	B1	8/2005	Elworthy	7,831,426	B2	11/2010	Bennett
6,964,023	B2	11/2005	Maes et al.	7,836,110	B1 *	11/2010	Schoenbach et al. .... 707/829
6,980,949	B2	12/2005	Ford	7,840,400	B2	11/2010	Lavi et al.
6,996,531	B2	2/2006	Korall et al.	7,873,519	B2	1/2011	Bennett
7,027,974	B1	4/2006	Busch et al.	7,873,654	B2	1/2011	Bernard
7,036,128	B1	4/2006	Julia et al.	7,881,936	B2	2/2011	Longé et al.
7,047,233	B1 *	5/2006	Humphreys et al. .... 707/752	7,904,331	B2 *	3/2011	Keil et al. .... 705/7.32
7,050,977	B1	5/2006	Bennett	7,912,702	B2	3/2011	Bennett
7,062,428	B2	6/2006	Hogenhout et al.	7,917,367	B2	3/2011	Di Cristo et al.
7,069,560	B1	6/2006	Cheyser et al.	7,917,497	B2	3/2011	Harrison et al.
7,092,928	B1	8/2006	Elad et al.	7,920,678	B2	4/2011	Cooper et al.
7,127,046	B1	10/2006	Smith et al.	7,930,168	B2	4/2011	Weng et al.
7,136,710	B1	11/2006	Hoffberg et al.	7,933,338	B1 *	4/2011	Choudhry et al. .... 375/240.26
7,137,126	B1	11/2006	Coffman et al.	7,949,529	B2	5/2011	Weider et al.
7,139,714	B2	11/2006	Bennett et al.	7,974,844	B2	7/2011	Sumita
7,200,559	B2	4/2007	Wang	7,983,917	B2	7/2011	Kennewick et al.
7,203,646	B2	4/2007	Bennett	7,983,997	B2	7/2011	Allen et al.
7,216,073	B2	5/2007	Lavi et al.	7,987,151	B2	7/2011	Schoff et al.
7,216,080	B2	5/2007	Tsiao et al.	8,000,453	B2	8/2011	Cooper et al.
7,225,125	B2	5/2007	Bennett et al.	8,005,679	B2	8/2011	Jordan et al.
7,233,904	B2	6/2007	Luisi	8,015,006	B2	9/2011	Kennewick et al.
7,277,854	B2	10/2007	Bennett et al.	8,041,570	B2	10/2011	Mirkovic et al.
7,290,039	B1	10/2007	Lisitsa et al.	8,055,638	B2 *	11/2011	Schechter et al. .... 707/705
7,324,947	B2	1/2008	Jordan et al.	8,055,708	B2	11/2011	Chitsaz et al.
7,349,953	B2	3/2008	Lisitsa et al.	8,060,524	B2 *	11/2011	Schechter et al. .... 707/768
7,376,556	B2	5/2008	Bennett	8,069,046	B2	11/2011	Kennewick et al.
7,376,645	B2	5/2008	Bernard	8,073,681	B2	12/2011	Baldwin et al.
7,379,874	B2	5/2008	Schmid et al.	8,082,153	B2	12/2011	Coffman et al.
7,386,449	B2	6/2008	Sun et al.	8,095,364	B2	1/2012	Longé et al.
7,392,185	B2	6/2008	Bennett	8,107,401	B2	1/2012	John et al.
7,398,209	B2	7/2008	Kennewick et al.	8,112,275	B2	2/2012	Kennewick et al.
7,403,938	B2	7/2008	Harrison et al.	8,200,663	B2 *	6/2012	Jones et al. .... 707/723
7,409,337	B1	8/2008	Potter et al.	8,554,767	B2 *	10/2013	Song et al. .... 707/732
7,415,100	B2	8/2008	Cooper et al.	8,918,330	B1 *	12/2014	Winkler et al. .... 705/14.16
7,426,467	B2	9/2008	Nashida et al.	2002/0065802	A1 *	5/2002	Uchiyama ..... 707/1
7,447,635	B1	11/2008	Konopka et al.	2002/0073079	A1 *	6/2002	Terheggen ..... 707/3
				2002/0152200	A1 *	10/2002	Krichilsky et al. .... 707/3
				2003/0028889	A1 *	2/2003	McCoskey et al. .... 725/91
				2003/0123443	A1 *	7/2003	Anwar ..... 370/392
				2005/0071332	A1 *	3/2005	Ortega et al. .... 707/4

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2005/0080625 A1 4/2005 Bennett et al.  
 2005/0119897 A1 6/2005 Bennett et al.  
 2006/0053095 A1\* 3/2006 Koch et al. 707/3  
 2006/0122834 A1 6/2006 Bennett  
 2006/0143007 A1 6/2006 Koh et al.  
 2006/0143236 A1\* 6/2006 Wu 707/104.1  
 2006/0248114 A1\* 11/2006 Anderson et al. 707/103 R  
 2007/0055529 A1 3/2007 Kanevsky et al.  
 2007/0088556 A1 4/2007 Andrew  
 2007/0100790 A1 5/2007 Cheyer et al.  
 2007/0112740 A1\* 5/2007 Geva 707/3  
 2007/0156677 A1\* 7/2007 Szabo 707/5  
 2007/0185917 A1 8/2007 Prahlad et al.  
 2007/0282595 A1 12/2007 Tunning et al.  
 2008/0009268 A1\* 1/2008 Ramer et al. 455/412.1  
 2008/0015864 A1 1/2008 Ross et al.  
 2008/0021708 A1 1/2008 Bennett et al.  
 2008/0034032 A1 2/2008 Healey et al.  
 2008/0052063 A1 2/2008 Bennett et al.  
 2008/0120112 A1 5/2008 Jordan et al.  
 2008/0140657 A1\* 6/2008 Azvine et al. 707/6  
 2008/0201227 A1\* 8/2008 Bakewell et al. 705/14  
 2008/0221903 A1 9/2008 Kanevsky et al.  
 2008/0228496 A1 9/2008 Yu et al.  
 2008/0247519 A1 10/2008 Abella et al.  
 2008/0300878 A1 12/2008 Bennett  
 2008/0301128 A1\* 12/2008 Gandert et al. 707/5  
 2009/0006343 A1\* 1/2009 Platt et al. 707/4  
 2009/0030800 A1 1/2009 Grois  
 2009/0058823 A1 3/2009 Kocienda  
 2009/0076796 A1 3/2009 Daraselia  
 2009/0100049 A1\* 4/2009 Cao 707/5  
 2009/0112647 A1\* 4/2009 Volkert 705/7  
 2009/0144153 A1\* 6/2009 Kondrk et al. 705/14  
 2009/0150156 A1 6/2009 Kennewick et al.  
 2009/0157401 A1 6/2009 Bennett  
 2009/0164441 A1 6/2009 Cheyer  
 2009/0171664 A1 7/2009 Kennewick et al.  
 2009/0199230 A1\* 8/2009 Kumar et al. 725/32  
 2009/0216805 A1\* 8/2009 Coffman et al. 707/104.1  
 2009/0240674 A1\* 9/2009 Wilde et al. 707/4  
 2009/0299745 A1 12/2009 Kennewick et al.  
 2010/0005081 A1 1/2010 Bennett  
 2010/0023320 A1 1/2010 Di Cristo et al.  
 2010/0036660 A1 2/2010 Bennett  
 2010/0042400 A1 2/2010 Block et al.  
 2010/0042603 A1\* 2/2010 Smyros et al. 707/4  
 2010/0095328 A1\* 4/2010 Hartung et al. 725/46  
 2010/0145700 A1 6/2010 Kennewick et al.  
 2010/0204986 A1 8/2010 Kennewick et al.  
 2010/0217604 A1 8/2010 Baldwin et al.  
 2010/0228540 A1 9/2010 Bennett  
 2010/0235341 A1 9/2010 Bennett  
 2010/0268680 A1\* 10/2010 Hangartner et al. 706/46  
 2010/0277579 A1 11/2010 Cho et al.  
 2010/0280983 A1 11/2010 Cho et al.  
 2010/0286985 A1 11/2010 Kennewick et al.  
 2010/0299142 A1 11/2010 Freeman et al.  
 2010/0299303 A1\* 11/2010 Horster et al. 706/52  
 2010/0306249 A1\* 12/2010 Hill et al. 707/769  
 2010/0312547 A1 12/2010 van Os et al.  
 2010/0313215 A1\* 12/2010 McCoskey et al. 725/31  
 2010/0318576 A1 12/2010 Kim  
 2010/0332235 A1 12/2010 David  
 2011/0035374 A1\* 2/2011 Vadrevu et al. 707/728  
 2011/0082688 A1 4/2011 Kim et al.  
 2011/0112827 A1 5/2011 Kennewick et al.  
 2011/0112921 A1 5/2011 Kennewick et al.  
 2011/0119049 A1 5/2011 Ylonen  
 2011/0125540 A1 5/2011 Jang et al.  
 2011/0131036 A1 6/2011 Di Cristo et al.  
 2011/0131045 A1 6/2011 Cristo et al.  
 2011/0137910 A1\* 6/2011 Hibino et al. 707/741  
 2011/0144999 A1 6/2011 Jang et al.  
 2011/0161076 A1 6/2011 Davis et al.

2011/0175810 A1 7/2011 Markovic et al.  
 2011/0184730 A1 7/2011 LeBeau et al.  
 2011/0225151 A1\* 9/2011 Annambhotla et al. 707/724  
 2011/0231182 A1 9/2011 Weider et al.  
 2011/0231188 A1 9/2011 Kennewick et al.  
 2011/0276396 A1\* 11/2011 Rathod 705/14.49  
 2011/0279368 A1 11/2011 Klein et al.  
 2011/0296463 A1\* 12/2011 Suslov 725/44  
 2011/0306426 A1 12/2011 Novak et al.  
 2012/0002820 A1 1/2012 Leichter  
 2012/0005181 A1\* 1/2012 Monteverde 707/706  
 2012/0016678 A1 1/2012 Gruber et al.  
 2012/0020490 A1 1/2012 Leichter  
 2012/0022787 A1\* 1/2012 LeBeau et al. 701/527  
 2012/0022857 A1 1/2012 Baldwin et al.  
 2012/0022860 A1 1/2012 Lloyd et al.  
 2012/0022868 A1 1/2012 LeBeau et al.  
 2012/0022869 A1 1/2012 Lloyd et al.  
 2012/0022870 A1 1/2012 Kristjansson et al.  
 2012/0022874 A1 1/2012 Lloyd et al.  
 2012/0022876 A1 1/2012 LeBeau et al.  
 2012/0023088 A1 1/2012 Cheng et al.  
 2012/0034904 A1 2/2012 LeBeau et al.  
 2012/0035908 A1 2/2012 LeBeau et al.  
 2012/0035924 A1 2/2012 Jitkoff et al.  
 2012/0035931 A1 2/2012 LeBeau et al.  
 2012/0035932 A1 2/2012 Jitkoff et al.

## FOREIGN PATENT DOCUMENTS

JP 2001 125896 5/2001  
 JP 2002 024212 1/2002  
 JP 2003517158 (A) 5/2003  
 JP 2009 036999 2/2009  
 KR 10-0776800 B1 11/2007  
 KR 10-0810500 B1 3/2008  
 KR 10 2008 109322 A 12/2008  
 KR 10 2009 086805 A 8/2009  
 KR 10-0920267 B1 10/2009  
 KR 10 2011 0113414 A 10/2011  
 WO WO 2011/088053 A2 7/2011

## OTHER PUBLICATIONS

Ambite, J.L., et al., "Design and Implementation of the CALO Query Manager," Copyright © 2006, American Association for Artificial Intelligence, (www.aaai.org), 8 pages.  
 Ambite, J.L., et al., "Integration of Heterogeneous Knowledge Sources in the CALO Query Manager," 2005, The 4th International Conference on Ontologies, DataBases, and Applications of Semantics (ODBASE), Agia Napa, Cyprus, [http://www.isi.edu/people/ambite/publications/integration\\_heterogeneous\\_knowledge\\_sources\\_cal\\_query\\_manager](http://www.isi.edu/people/ambite/publications/integration_heterogeneous_knowledge_sources_cal_query_manager), 18 pages.  
 Belvin, R. et al., "Development of the HRL Route Navigation Dialogue System," 2001, In Proceedings of the First International Conference on Human Language Technology Research, Paper, Copyright © 2001 HRL Laboratories, LLC, <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.10.6538>, 5 pages.  
 Berry, P. M., et al. "PTIME: Personalized Assistance for Calendar- ing," ACM Transactions on Intelligent Systems and Technology, vol. 2, No. 4, Article 40, Publication date: Jul. 2011, 40:1-22, 22 pages.  
 Butcher, M., "EVI arrives in town to go toe-to-toe with Siri," Jan. 23, 2012, <http://techcrunch.com/2012/01/23/evi-arrives-in-town-to-go-toe-to-toe-with-siri/>, 2 pages.  
 Chen, Y., "Multimedia Siri Finds And Plays Whatever You Ask For," Feb. 9, 2012, <http://www.psfk.com/2012/02/multimedia-siri.html>, 9 pages.  
 Cheyer, A. et al., "Spoken Language and Multimodal Applications for Electronic Realities," © Springer-Verlag London Ltd, Virtual Reality 1999, 3:1-15, 15 pages.  
 Cutkosky, M. R. et al., "PACT: An Experiment in Integrating Concurrent Engineering Systems," Journal, Computer, vol. 26 Issue 1, Jan. 1993, IEEE Computer Society Press Los Alamitos, CA, USA, <http://dl.acm.org/citation.cfm?id=165320>, 14 pages.  
 Elio, R. et al., "On Abstract Task Models and Conversation Policies," [http://webdocs.cs.ualberta.ca/~ree/publications/papers2/ATS\\_AA99.pdf](http://webdocs.cs.ualberta.ca/~ree/publications/papers2/ATS_AA99.pdf), 10 pages.

(56)

**References Cited****OTHER PUBLICATIONS**

- Ericsson, S. et al., "Software illustrating a unified approach to multimodality and multilinguality in the in-home domain," Dec. 22, 2006, Talk and Look: Tools for Ambient Linguistic Knowledge, [http://www.talk-project.eurice.eu/fileadmin/talk/publications\\_public/deliverables\\_public/D1\\_6.pdf](http://www.talk-project.eurice.eu/fileadmin/talk/publications_public/deliverables_public/D1_6.pdf), 127 pages.
- Evi, "Meet Evi: the one mobile app that provides solutions for your everyday problems," Feb. 8, 2012, <http://www.evi.com/>, 3 pages.
- Feigenbaum, E., et al., "Computer-assisted Semantic Annotation of Scientific Life Works," 2007, <http://tomgruber.org/writing/stanford-cs300.pdf>, 22 pages.
- Gannes, L., "Alfred App Gives Personalized Restaurant Recommendations," allthingsd.com, Jul. 18, 2011, <http://allthingsd.com/20110718/alfred-app-gives-personalized-restaurant-recommendations/>, 3 pages.
- Gautier, P. O., et al. "Generating Explanations of Device Behavior Using Compositional Modeling and Causal Ordering," 1993, <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.42.8394>, 9 pages.
- Gervasio, M. T., et al., Active Preference Learning for Personalized Calendar Scheduling Assistance, Copyright © 2005, <http://www.ai.sri.com/~gervasio/pubs/gervasio-iiui05.pdf>, 8 pages.
- Glass, A., "Explaining Preference Learning," 2006, <http://cs229.stanford.edu/proj2006/Glass-ExplainingPreferenceLearning.pdf>, 5 pages.
- Gruber, T. R., et al., "An Ontology for Engineering Mathematics," In Jon Doyle, Piero Torasso, & Erik Sandewall, Eds., Fourth International Conference on Principles of Knowledge Representation and Reasoning, Gustav Stresemann Institut, Bonn, Germany, Morgan Kaufmann, 1994, <http://www-ksl.stanford.edu/knowledge-sharing/papers/engmath.html>, 22 pages.
- Gruber, T. R., "A Translation Approach to Portable Ontology Specifications," Knowledge Systems Laboratory, Stanford University, Sep. 1992, Technical Report KSL 92-71, Revised Apr. 1993, 27 pages.
- Gruber, T. R., "Automated Knowledge Acquisition for Strategic Knowledge," Knowledge Systems Laboratory, Machine Learning, 4, 293-336 (1989), 44 pages.
- Gruber, T. R., "(Avoiding) the Travesty of the Commons," Presentation at NPUC 2006, New Paradigms for User Computing, IBM Almaden Research Center, Jul. 24, 2006, <http://tomgruber.org/writing/avoiding-travesty.htm>, 52 pages.
- Gruber, T. R., "Big Think Small Screen: How semantic computing in the cloud will revolutionize the consumer experience on the phone," Keynote presentation at Web 3.0 conference, Jan. 27, 2010, <http://tomgruber.org/writing/web30jan2010.htm>, 41 pages.
- Gruber, T. R., "Collaborating around Shared Content on the WWW," W3C Workshop on WWW and Collaboration, Cambridge, MA, Sep. 11, 1995, <http://www.w3.org/Collaboration/Workshop/Proceedings/P9.html>, 1 page.
- Gruber, T. R., "Collective Knowledge Systems: Where the Social Web meets the Semantic Web," Web Semantics: Science, Services and Agents on the World Wide Web (2007), doi:10.1016/j.websem.2007.11.011, keynote presentation given at the 5th International Semantic Web Conference, Nov. 7, 2006, 19 pages.
- Gruber, T. R., "Where the Social Web meets the Semantic Web," Presentation at the 5th International Semantic Web Conference, Nov. 7, 2006, 38 pages.
- Gruber, T. R., "Despite our Best Efforts, Ontologies are not the Problem," AAAI Spring Symposium, Mar. 2008, <http://tomgruber.org/writing/aaai-ss08.htm>, 40 pages.
- Gruber, T. R., "Enterprise Collaboration Management with Intraspect," Intraspect Software, Inc., Intraspect Technical White Paper Jul. 2001, 24 pages.
- Gruber, T. R., "Every ontology is a treaty—a social agreement—among people with some common motive in sharing," Interview by Dr. Miltiadis D. Lytras, Official Quarterly Bulletin of AIS Special Interest Group on Semantic Web and Information Systems, vol. 1, Issue 3, 2004, <http://www.sigsemis.org> 1, 5 pages.
- Gruber, T. R., et al., "Generative Design Rationale: Beyond the Record and Replay Paradigm," Knowledge Systems Laboratory, Stanford University, Dec. 1991, Technical Report KSL 92-59, updated Feb. 1993, 24 pages.
- Gruber, T. R., "Helping Organizations Collaborate, Communicate, and Learn," Presentation to NASA Ames Research, Mountain View, CA, Mar. 2003, <http://tomgruber.org/writing/organizational-intelligence-talk.htm>, 30 pages.
- Gruber, T. R., "Intelligence at the Interface: Semantic Technology and the Consumer Internet Experience," Presentation at Semantic Technologies conference (SemTech08), May 20, 2008, <http://tomgruber.org/writing.htm>, 40 pages.
- Gruber, T. R., Interactive Acquisition of Justifications: Learning "Why" by Being Told "What" Knowledge Systems Laboratory, Stanford University, Oct. 1990, Technical Report KSL 91-17, Revised Feb. 1991, 24 pages.
- Gruber, T. R., "It Is What It Does: The Pragmatics of Ontology for Knowledge Sharing," (c) 2000, 2003, [http://www.cidoc-crm.org/docs/symposium\\_presentations/gruber\\_cidoc-ontology-2003.pdf](http://www.cidoc-crm.org/docs/symposium_presentations/gruber_cidoc-ontology-2003.pdf), 21 pages.
- Gruber, T. R., et al., "Machine-generated Explanations of Engineering Models: A Compositional Modeling Approach," (1993) In Proc. International Joint Conference on Artificial Intelligence, <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.34.930>, 7 pages.
- Gruber, T. R., "2021: Mass Collaboration and the Really New Economy," TNTY Futures, the newsletter of The Next Twenty Years series, vol. 1, Issue 6, Aug. 2001, <http://www.tnty.com/newsletter/futures/archive/v01-05business.html>, 5 pages.
- Gruber, T. R., et al., "NIKE: A National Infrastructure for Knowledge Exchange," Oct. 1994, <http://www.eit.com/papers/nike/nike.html> and [nike.ps](http://www.nike.ps), 10 pages.
- Gruber, T. R., "Ontologies, Web 2.0 and Beyond," Apr. 24, 2007, Ontology Summit 2007, <http://tomgruber.org/writing/ontology-social-web-keynote.pdf>, 17 pages.
- Gruber, T. R., "Ontology of Folksonomy: A Mash-up of Apples and Oranges," Originally published to the web in 2005, Int'l Journal on Semantic Web & Information Systems, 3(2), 2007, 7 pages.
- Gruber, T. R., "Siri, a Virtual Personal Assistant—Bringing Intelligence to the Interface," Jun. 16, 2009, Keynote presentation at Semantic Technologies conference, Jun. 2009, <http://tomgruber.org/writing/semtech09.htm>, 22 pages.
- Gruber, T. R., "TagOntology," Presentation to Tag Camp, www.tagcamp.org, Oct. 29, 2005, 20 pages.
- Gruber, T. R., et al., "Toward a Knowledge Medium for Collaborative Product Development," In Artificial Intelligence in Design 1992, from Proceedings of the Second International Conference on Artificial Intelligence in Design, Pittsburgh, USA, Jun. 22-25, 1992, 19 pages.
- Gruber, T. R., "Toward Principles for the Design of Ontologies Used for Knowledge Sharing," In International Journal Human-Computer Studies 43, p. 907-928, substantial revision of paper presented at the International Workshop on Formal Ontology, Mar. 1993, Padova, Italy, available as Technical Report KSL 93-04, Knowledge Systems Laboratory, Stanford University, further revised Aug. 23, 1993, 23 pages.
- Guzzoni, D., et al., "Active, A Platform for Building Intelligent Operating Rooms," Surgetica 2007 Computer-Aided Medical Interventions: tools and applications, pp. 191-198, Paris, 2007, Sauramps Médical, <http://Isro.epfl.ch/page-68384-en.html>, 8 pages.
- Guzzoni, D., et al., "Active, A Tool for Building Intelligent User Interfaces," ASC 2007, Palma de Mallorca, <http://Isro.epfl.ch/page-34241.html>, 6 pages.
- Guzzoni, D., et al., "Modeling Human-Agent Interaction with Active Ontologies," 2007, AAAI Spring Symposium, Interaction Challenges for Intelligent Assistants, Stanford University, Palo Alto, California, 8 pages.
- Hardawar, D., "Driving app Waze builds its own Siri for hands-free voice control," Feb. 9, 2012, <http://venturebeat.com/2012/02/09/driving-app-waze-builds-its-own-siri-for-hands-free-voice-control/>, 4 pages.

(56)

## References Cited

## OTHER PUBLICATIONS

Intraspect Software, "The Intraspect Knowledge Management Solution: Technical Overview," <http://tomgruber.org/writing/intraspect-whitepaper-1998.pdf>, 18 pages.

Julia, L., et al., Un éditeur interactif de tableaux dessinés à main levée (An Interactive Editor for Hand-Sketched Tables), *Traitement du Signal* 1995, vol. 12, No. 6, 8 pages. No English Translation Available.

Karp, P. D., "A Generic Knowledge-Base Access Protocol," May 12, 1994, <http://lecture.cs.buu.ac.th/~f50353/Document/gfp.pdf>, 66 pages.

Lemon, O., et al., "Multithreaded Context for Robust Conversational Interfaces: Context-Sensitive Speech Recognition and Interpretation of Corrective Fragments," Sep. 2004, *ACM Transactions on Computer-Human Interaction*, vol. 11, No. 3, 27 pages.

Leong, L., et al., "CASIS: A Context-Aware Speech Interface System," IUT'05, Jan. 9-12, 2005, Proceedings of the 10th international conference on Intelligent user interfaces, San Diego, California, USA, 8 pages.

Lieberman, H., et al., "Out of context: Computer systems that adapt to, and learn from, context," 2000, *IBM Systems Journal*, vol. 39, Nos. 3/4, 2000, 16 pages.

Lin, B., et al., "A Distributed Architecture for Cooperative Spoken Dialogue Agents with Coherent Dialogue State and History," 1999, <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.42.272>, 4 pages.

McGuire, J., et al., "SHADE: Technology for Knowledge-Based Collaborative Engineering," 1993, *Journal of Concurrent Engineering: Applications and Research (CERA)*, 18 pages.

Milward, D., et al., "D2.2: Dynamic Multimodal Interface Reconfiguration," Talk and Look: Tools for Ambient Linguistic Knowledge, Aug. 8, 2006, [http://www.ihmc.us/users/nblaylock/Pubs/Files/talk\\_d2.2.pdf](http://www.ihmc.us/users/nblaylock/Pubs/Files/talk_d2.2.pdf), 69 pages.

Mitra, P., et al., "A Graph-Oriented Model for Articulation of Ontology Interdependencies," 2000, <http://ilpubs.stanford.edu:8090/442/1/2000-20.pdf>, 15 pages.

Moran, D. B., et al., "Multimodal User Interfaces in the Open Agent Architecture," Proc. of the 1997 International Conference on Intelligent User Interfaces (IUI97), 8 pages.

Mozar, M., "An Intelligent Environment Must be Adaptive," Mar./Apr. 1999, *IEEE Intelligent Systems*, 3 pages.

Mühlhäuser, M., "Context Aware Voice User Interfaces for Workflow Support," Darmstadt 2007, <http://tuprints.ulb.tu-darmstadt.de/876/1/PhD.pdf>, 254 pages.

Naone, E., "TR10: Intelligent Software Assistant," Mar.-Apr. 2009, *Technology Review*, [http://www.technologyreview.com/printer\\_friendly\\_article.aspx?id=22117](http://www.technologyreview.com/printer_friendly_article.aspx?id=22117), 2 pages.

Neches, R., "Enabling Technology for Knowledge Sharing," Fall 1991, *AI Magazine*, pp. 37-56, (21 pages).

Nóth, E., et al., "VerbMobil: The Use of Prosody in the Linguistic Components of a Speech Understanding System," *IEEE Transactions on Speech and Audio Processing*, vol. 8, No. 5, Sep. 2000, 14 pages.

Rice, J., et al., "Monthly Program: Nov. 14, 1995," The San Francisco Bay Area Chapter of ACM SIGCHI, <http://www.baychi.org/calendar/19951114/>, 2 pages.

Rice, J., et al., "Using the Web Instead of a Window System," Knowledge Systems Laboratory, Stanford University, <http://tomgruber.org/writing/ksl-95-69.pdf>, 14 pages.

Rivlin, Z., et al., "Maestro: Conductor of Multimedia Analysis Technologies," 1999 SRI International, Communications of the Association for Computing Machinery (CACM), 7 pages.

Sheth, A., et al., "Relationships at the Heart of Semantic Web: Modeling, Discovering, and Exploiting Complex Semantic Relationships," Oct. 13, 2002, *Enhancing the Power of the Internet: Studies in Fuzziness and Soft Computing*, SpringerVerlag, 38 pages.

Simonite, T., "One Easy Way to Make Siri Smarter," Oct. 18, 2011, *Technology Review*, [http://www.technologyreview.com/printer\\_friendly\\_article.aspx?id=38915](http://www.technologyreview.com/printer_friendly_article.aspx?id=38915), 2 pages.

Stent, A., et al., "The CommandTalk Spoken Dialogue System," 1999, <http://acl.ldc.upenn.edu/P/P99/P99-1024.pdf>, 8 pages.

Tofel, K., et al., "SpeakTolt: A personal assistant for older iPhones, iPads," Feb. 9, 2012, <http://gigaom.com/apple/speaktoit-siri-for-older-iphones-ipads/>, 7 pages.

Tucker, J., "Too lazy to grab your TV remote? Use Siri instead," Nov. 30, 2011, <http://www.engadget.com/2011/11/30/too-lazy-to-grab-your-tv-remote-use-siri-instead/>, 8 pages.

Tur, G., et al., "The CALO Meeting Speech Recognition and Understanding System," 2008, *Proc. IEEE Spoken Language Technology Workshop*, 4 pages.

Tur, G., et al., "The-CALO-Meeting-Assistant System," *IEEE Transactions on Audio, Speech, and Language Processing*, vol. 18, No. 6, Aug. 2010, 11 pages.

Vlingo, "Vlingo Launches Voice Enablement Application on Apple App Store," Vlingo press release dated Dec. 3, 2008, 2 pages.

YouTube, "Knowledge Navigator," 5:34 minute video uploaded to YouTube by Knownav on Apr. 29, 2008, [http://www.youtube.com/watch?v=QRH8eimU\\_20](http://www.youtube.com/watch?v=QRH8eimU_20) on Aug. 3, 2006, 1 page.

YouTube, "Send Text, Listen To and Send E-Mail 'By Voice' www.voiceassist.com," 2:11 minute video uploaded to YouTube by VoiceAssist on Jul. 30, 2009, <http://www.youtube.com/watch?v=0tEU61nHHA4>, 1 page.

YouTube, "Text'nDrive App Demo—Listen and Reply to your Messages by Voice while Driving!," 1:57 minute video uploaded to YouTube by TextnDrive on Apr. 27, 2010, <http://www.youtube.com/watch?v=WaGfzoHsAMw>, 1 page.

YouTube, "Voice On The Go (BlackBerry)," 2:51 minute video uploaded to YouTube by VoiceOnTheGo on Jul. 27, 2009, <http://www.youtube.com/watch?v=pJqpWgQS98w>, 1 page.

International Search Report and Written Opinion dated Nov. 29, 2011, received in International Application No. PCT/US2011/20861, which corresponds to U.S. Appl. No. 12/987,982, 15 pages (Thomas Robert Gruber).

Glass, J., et al., "Multilingual Spoken-Language Understanding in the MIT Voyager System," Aug. 1995, <http://groups.csail.mit.edu/sls/publications/1995/speechcomm95-voyager.pdf>, 29 pages.

Goddeau, D., et al., "A Form-Based Dialogue Manager for Spoken Language Applications," Oct. 1996, <http://phasedance.com/pdf/icslp96.pdf>, 4 pages.

Goddeau, D., et al., "Galaxy: A Human-Language Interface to On-Line Travel Information," 1994 International Conference on Spoken Language Processing, Sep. 18-22, 1994, Pacific Convention Plaza Yokohama, Japan, 6 pages.

Meng, H., et al., "Wheels: A Conversational System in the Automobile Classified Domain," Oct. 1996, <http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.16.3022>, 4 pages.

Phoenix Solutions, Inc. v. West Interactive Corp., Document 40, Declaration of Christopher Schmandt Regarding the MIT Galaxy System dated Jul. 2, 2010, 162 pages.

Seneff, S., et al., "A New Restaurant Guide Conversational System: Issues in Rapid Prototyping for Specialized Domains," Oct. 1996, [citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.16...rep...](http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.16...rep...), 4 pages.

Vlingo InCar, "Distracted Driving Solution with Vlingo InCar," 2:38 minute video uploaded to YouTube by Vlingo Voice on Oct. 6, 2010, <http://www.youtube.com/watch?v=Vqs8XfXgz4>, 2 pages.

Zue, V., "Conversational Interfaces: Advances and Challenges," Sep. 1997, <http://www.cs.cmu.edu/~dod/papers/zue97.pdf>, 10 pages.

Zue, V. W., "Toward Systems that Understand Spoken Language," Feb. 1994, ARPA Strategic Computing Institute, © 1994 IEEE, 9 pages.

U.S. Appl. No. 61/350,185, filed Jun. 1, 2010, 17 pages.

\* cited by examiner






FIG. 1







FIG. 3








FIG. 4B




FIG. 5





FIG. 6



700'

Search

>

704

Release

Category

All

Date

All

Star Rating

All

Price

All

Type

Show All

Reset

718'

722

Graphic

[Developer Name]

[Category]

[Date Released/Updated]

[rating/ # rating]

720

726

[Price]

Buy

724

[Developer Name]

[Category]

[Date Released/Updated]

[rating/ # rating]

728

[Price]

Buy

Graphic

[Developer Name]

[Category]

[Date Released/Updated]

[rating/ # rating]

720

720

[Price]

Buy

Graphic

[Developer Name]

[Category]

[Date Released/Updated]

[rating/ # rating]

720

720

[Price]

Buy

FIG. 7B

700"

730

702

> Graphics

Search

Release

Category

Date

Star Rating

Price

Type

All

All

All

Show All

Reset

1-4 of 1000

732

Sort by:

Relevance

734

704'

718"

Graphic	<div>[Developer Name]</div> <div>[Category]</div> <div>[Date Released/Updated]</div> <div>[rating/ # rating]</div> <div>[Price]</div> <div>Buy</div>	720
Graphic	<div>[Developer Name]</div> <div>[Category]</div> <div>[Date Released/Updated]</div> <div>[rating/ # rating]</div> <div>[Price]</div> <div>Buy</div>	720

FIG. 7C

700"

730

Search

> Graphics

706

Category

Games

Release Date

This Month

732' 708

710

Star Rating

5 Stars

712

Price

All

714

Type

Show All

716

Reset

Sort by:

Relevance

734

716

704"

718"

<div>1-4 of 210</div> <div>Graphic</div> <div> <div>[Developer Name]</div> <div>[Category]</div> <div>[Date Released/Updated]</div> <div>[rating/ # rating]</div> </div> <div> <div>[Price]</div> <div>Buy</div> </div> <div>720</div>	<div>Graphic</div> <div> <div>[Developer Name]</div> <div>[Category]</div> <div>[Date Released/Updated]</div> <div>[rating/ # rating]</div> </div> <div> <div>[Price]</div> <div>Buy</div> </div> <div>720</div>
<div>Graphic</div> <div> <div>[Developer Name]</div> <div>[Category]</div> <div>[Date Released/Updated]</div> <div>[rating/ # rating]</div> </div> <div> <div>[Price]</div> <div>Buy</div> </div> <div>720</div>	<div>Graphic</div> <div> <div>[Developer Name]</div> <div>[Category]</div> <div>[Date Released/Updated]</div> <div>[rating/ # rating]</div> </div> <div> <div>[Price]</div> <div>Buy</div> </div> <div>720</div>

FIG. 7D



## CUSTOMIZED SEARCH OR ACQUISITION OF DIGITAL MEDIA ASSETS

### BACKGROUND OF THE INVENTION

Computerized searching is commonly used for searching through electronic files or searching of the World Wide Web. Searching can be performed using key words supplied by a user that is requesting a search. Upon receiving the key words for the search, a computer can perform a search for matching electronic files.

The results of the search are typically presented as a list of electronic files that include the keyword that has been searched. The electronic files in the list can be referred to as matching electronic files. The ordering of the matching electronic files within the list can be random, alphabetical, or by attribute (e.g., date, size, popularity or user rating). The results of the search are the same regardless of the user initiating the search.

Mobile computing devices are typically dependent upon network availability to access network-based resources (e.g., electronic files on the World Wide Web) or to communicate with other remote computing devices. Many users rely on constant network access to be able to communicate with other computing devices. With wireless networks, network access can be unavailable at certain locations or when there is an excess amount of network congestion. Network unavailability can frustrate users because the mobile computing devices have substantially curtailed capabilities when network access is unavailable.

Thus, there is a need for improved techniques to operate a computing device, such as a mobile computing device, so that search and/or network access capabilities are enhanced.

### SUMMARY

The invention pertains to improved techniques for using usage data. The usage data can pertain to a user of an electronic device. The usage data can be monitored and recorded on the electronic device. The improved techniques are particularly useful when the electronic device is a mobile electronic device. In one embodiment, the usage data can be used to enhance searching of digital assets, such as digital media assets, resident at a local or remote repository. In another embodiment, the usage data can be used to determine content to be resident locally on the electronic device. In still another embodiment, the usage data can be used to present (e.g., display) information on the electronic device.

The invention can be implemented in numerous ways, including as a method, system, device, apparatus (including computer readable medium and graphical user interface). Several embodiments of the invention are discussed below.

As a method for providing digital media content to an electronic device, one embodiment can, for example, include at least monitoring usage of a first digital media asset having a plurality of levels or chapters, and comparing the usage of the first digital media asset to at least one trigger point. The embodiment can also include retrieving additional digital media data for use on the electronic device if the comparing determines that the usage of the first digital media asset exceeds the at least one trigger point.

As a computer readable storage medium, the computer readable storage medium can include at least computer program code executable by an electronic device to provide digital media content to the electronic device. According to one embodiment, the computer program code stored on the computer readable storage medium can, for example, include

at least computer program code for monitoring usage of a first digital media asset having a plurality of levels or chapters, computer program code for comparing the usage of the first digital media asset to at least one trigger point, and computer program code for retrieving additional digital media data for use on the electronic device if the computer program code for comparing determines that the usage of the first digital media asset exceeds the at least one trigger point.

As a method for processing a user search, one embodiment can, for example, include at least receiving a user search request from an electronic device, where the user search request includes one or more search criteria. The embodiment also can include searching a database in accordance with the one or more search criteria to obtain search results, where the database includes digital asset information pertaining to a plurality of digital media assets. Furthermore, the embodiment can include accessing usage data pertaining to the electronic device or its user, ranking the search results based at least in part on the usage data, and presenting the ranked search results via the electronic device.

As a computer readable storage medium, the computer readable storage medium can include at least computer program code executable by an electronic device for processing a user search. According to one embodiment, the computer program code stored on the computer readable storage medium can, for example, include at least computer program code for receiving a user search request from an electronic device, the user search request including search one or more search criteria; computer program code for searching a database in accordance with the one or more search criteria to obtain search results, the database including digital asset information pertaining to a plurality of digital media assets; computer program code for accessing usage data pertaining to the electronic device or its user; computer program code for ranking the search results based at least in part on the usage data; and computer program code for presenting the ranked search results via the electronic device.

Other aspects and advantages of the invention will become apparent from the following detailed description taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of the invention.

### BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be readily understood by the following detailed description in conjunction with the accompanying drawings, wherein like reference numerals designate like elements, and in which:

FIG. 1 is a block diagram of a digital asset access system according to one embodiment.

FIG. 2A is a block diagram of a user computing device according to one embodiment.

FIG. 2B is an illustrative view of a digital asset representation according to one embodiment.

FIG. 3 is a flow diagram of a data acquisition process according to one embodiment.

FIGS. 4A and 4B are flow diagrams of a data retrieval process according to one embodiment.

FIG. 5 is a block diagram of a user computing device according to another embodiment.

FIG. 6 is a flow diagram of a customized search process according to one embodiment.

FIGS. 7A-7D illustrate exemplary search screens of a search GUI according to one embodiment.

### DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

The invention pertains to improved techniques for using usage data. The usage data can pertain to a user of an elec-

tronic device. The usage data can be monitored and recorded on the electronic device. The improved techniques are particularly useful when the electronic device is a mobile electronic device. In one embodiment, the usage data can be used to enhance searching of digital assets, such as digital media assets, resident at a local or remote repository. In another embodiment, the usage data can be used to determine content to be resident locally on the electronic device. In still another embodiment, the usage data can be used to present (e.g., display) information on the electronic device.

The electronic device can, for example, be a computing device. Examples of a computing device include a personal computer (e.g., desktop computer, notebook computer, netbook computer, etc.), or a portable handheld electronic device (e.g., Portable Digital Assistant (PDA), portable media player, multi-function mobile telephone, etc.).

Several embodiments of the invention are discussed below with reference to FIGS. 1-7D. However, those skilled in the art will readily appreciate that the detailed description given herein with respect to these figures is for explanatory purposes as the invention can extend beyond these limited embodiments.

Electronic devices, in particular mobile electronic devices, have limited data storage capacity and users do not always plan ahead to have all the needed electronic data resident on their mobile electronic device. Network access, if available, enables access to digital data from anywhere via a network that would otherwise not be readily available. However, if network access is unreliable or unavailable, a user that has not properly planned ahead may be stuck in a situation where desired or needed data is unavailable. Also, if systems are desirous of providing data to users of mobile electronic devices, these systems are also dependent on network availability.

According to one aspect, predictive digital data acquisition can be used on electronic devices, in particular, mobile electronic devices. The predictive digital data acquisition can be used to acquire and at least temporarily store digital data that may be later desired, needed, promoted or offered. The prediction of digital data to be provided on a mobile electronic device can be determined using usage data that has been obtained through monitoring usage of the mobile electronic device. Thus, even though network access (e.g., wireless network) is unavailable, a user of a mobile electronic device is able to access digital data, such as digital assets, that have been predictively stored on the mobile electronic device.

The digital data being predictively acquired and stored can be considered to be cached at an electronic device, such as a mobile electronic device. A cache represents data storage that is provided for reduced memory access times. The digital data being "cached" can pertain to a plurality of digital assets, which can represent one or more types of digital assets.

One example of predictive digital data acquisition is for audiobooks. Usage data can, for example, concern data that is obtained by monitoring a user's usage of an e-book (or audiobook). In such an example, the usage data can estimate where the user is in "reading" the e-book via an electronic device. When the usage data indicates that the reader is nearing the end of the e-book, the predictive digital data acquisition can operate to acquire related digital data from one or more remote servers. The related digital data can be received via a network and stored on the electronic device. Thereafter, some or all of the related digital data can be presented to the user via the electronic device. The user can then subsequently preview, purchase, play, or review some or all of the related digital data without being then dependent on network availability. For instance, as a user completes a first e-book, a

second e-book can be pre-stored on the electronic device in advance of any user request for such digital data. Hence, the second e-book is readily available at the electronic device regardless of network availability.

Another example of predictive digital data acquisition is for software games. Usage data can, for example, concern data that is obtained by monitoring a user's usage of a software game to estimate where the user is in "completing" the software game via an electronic device. When the usage data indicates that the user is close to "completing" the software game (such as approaching the end of the software game or approaching the need for another level, tool, feature, etc.), the predictive digital data acquisition can operate to acquire related digital data from one or more remote servers. The related digital data can be received and stored on the electronic device in advance and when the network is available. Thereafter, some or all of the related digital data can be utilized with the software game to the user via the electronic device. The user can then upgrade the software game or install another software game (e.g., a sequel game, a recommended game, etc.) using the related digital data efficiently without any need for network availability. For instance, as a user completes a first software game, an extension to the first software game or a second software game can be pre-stored on the electronic device in advance of any user request for such digital data.

Yet another example of predictive digital data acquisition is for podcasts or television shows. Usage data can, for example, concern data that is obtained by monitoring a user's usage of a particular podcast or television show. The usage data can estimate where the user is in viewing (or playback) of the particular podcast or television show via an electronic device (e.g., play position). When the usage data indicates that the user is nearing the end of the particular podcast or television show, the predictive digital data acquisition can operate to acquire related digital data from one or more remote servers. For example, the related digital data can pertain to a next or subsequent podcast or television show. The related digital data can be received via a network and stored on the electronic device. Thereafter, some or all of the related digital data can be presented to the user via the electronic device. The user can then preview, purchase, play, review some or all of the related digital data without being then dependent on network availability. For instance, as a user completes an episode or television show, a next episode or television show can be pre-stored on the electronic device in advance of any user request for such digital data such that it is available when the user completes the episode or television show.

More generally, as another example, usage data can be used to customize recommendations for a user. The user's electronic device can then operate to acquire digital data associated with the recommendations. The recommendations can be of various different kinds of digital data. A recommendation can also be for a preview of a digital media asset.

FIG. 1 is a block diagram of a digital asset access system 100 according to one embodiment. The digital asset access system 100 can include an online media server 102. The online media server 102 provides access to various digital assets. More particularly, the online media server 102 can manage access to store digital assets. The stored digital assets can be stored at the online media server 102 or stored remotely at a storage server (not shown). In one embodiment, the online media server 102 can enable networked-based access by computing devices for searching, browsing, purchasing, previewing or downloading the various stored digital assets.

5

The digital asset access system **100** also makes use of a network **104**. The network **104** can include one or more wired networks and/or one or more wireless networks to facilitate data transfer between the online media server **102** and one or more user computing devices **106**.

According to one embodiment, the user computing devices **106** can each independently monitor usage data. The usage data can be stored and thus reside on the user computing device **106** and/or on the online media server **102** (or some other remote storage device). The usage data can be utilized to customize digital assets (or sets thereof) being provided to the particular user computing device **106**. The determination of the customized digital assets can be performed at the user computing device **106** or at the online media server **102**.

As one example, during a search through a plurality of digital assets, the usage data associated with the particular user computing device **106** that initiated the search can have the results of the search presented at the user computing device **106** such that the search results are customized for the user. For example, the user data associated with the user computing device **106** may indicate that the associated user is more interested in digital assets pertaining to television (TV) shows than digital assets pertaining to music. Hence, for such a user, the associated user computing device **106** can present the search results such that the TV shows within the results of the search can be more prominently presented to the user via the user computing device **106**.

As another example, user computing device **106** can monitor usage data to intelligently maintain predicted digital assets on the user computing device **106**. Here, in one embodiment, a portion of the local digital storage available to store digital assets at the user computing device **106** can be utilized to store digital assets that are predicted to be of potential interest to the user associated with the user computing device **106**. In this case, those predicted digital assets can vary as the user data varies. In one implementation, the predicted digital assets can be acquired from the online media server **102** and electronically downloaded to the user computing device **106**. The downloading of the predicted digital assets can be performed in a background mode since the user has at this time not made a specific request for these predicted digital assets.

FIG. 2A is a block diagram of a user computing device **200** according to one embodiment. The user computing device **200** can, for example, represent the user computing device **106** illustrated in FIG. 1.

The user computing device **200** includes a central controller **202**. The central controller **202**, for example, can include a central processing unit (CPU). The central controller **202** can include support for media playback. Namely, the central controller **202** can include or operate to provide a media play module **204**. The media play module **204** can operate to play a digital asset, such as a digital media asset, on the user computing device **200**.

The user computing device **200** can include a local data storage **206**. The local data storage **206** can store one or more digital assets, such as digital media assets. The media play module **204** can be controlled by the central controller **202** to play one or more of the digital assets stored in the local data storage **206**. The output of the media play module **204** can be directed by the central controller **202** to an output device **208**. An input device **210**, such as a user input device, can be used to supply user inputs to the central controller **202** to designate a digital asset to be played by the media play module **204**. The input device **210** can also be used to provide other user inputs to the central controller **202**.

The user computing device **200** can also include a network interface **212**. The network interface **212** can enable the user

6

computing device **200** to interact with an online media server via a network, such as the online media server **102** and network **104** illustrated in FIG. 1. Consequently, the user computing device **200** can send commands, receive responses and/or receive digital assets from the online media server **102**. The digital asset(s) being received from the online media **102** via the network can be stored to the local data storage **206**. Alternatively, the digital asset(s) being received from the online media server **102** can be streamed to an output device **208**.

The user computing device **200** can also include a usage monitor **214**. The usage monitor **214** is provided within the user computing device **200** to monitor usage by a user of the user computing device **200**. In doing so, the usage monitor **214** can record usage data **216**. The usage data **216** can, in one embodiment, be stored within the usage monitor **214** as shown in FIG. 2A. Alternatively or additionally, the usage data **216** can be stored to the local data storage **206**.

The user computing device **200** can also include a predicted asset manager **218**. The predicted asset manager **218** can predict one or more digital assets that are likely to be of interest to the user of the user computing device **200**. The predicted asset manager **218** can make use of the usage data **216** acquired by the usage monitor **214**. The usage data **216** can be acquired and manipulated or updated over time to provide a reliable data set used to predict digital assets likely to be of interest to the user. These predicted digital assets can be obtained from a remote server, such as the online media server **102** via the network interface **212**. Upon receiving the predicted digital assets, the predicted digital assets can be stored to the local data storage **206**. Typically, as noted above, a portion of the local data storage **206** can be dedicated to storage of predicted digital assets. Hence, it may be necessary to delete or remove a portion of the predicted digital assets previously stored in the dedicated portion of the local data storage **206** so that more recently predicted digital assets can be stored in the portion of the local data storage **206**.

FIG. 2B is an illustrative view of a digital asset representation **250** according to one embodiment. The digital asset representation **250** represents a digital asset having a sequential arrangement of sections. These sections can correspond to chapters, tracks, episodes, shows, levels and the like. In the example illustrated in FIG. 2B, the digital asset representation includes six (6) sections. As a user consumes a digital asset, such as through playing the digital asset, a current user position **252** can be recorded and associated with the particular digital asset. Hence, if the user consumes (e.g., views, hears, etc.) a portion of the digital asset and then stops, then when the user later begins to again consume a subsequent portion of the digital media asset, the user can continue at the point at which he previously stopped. The starting position for resuming the consumption of the digital asset can be noted and recorded by the current user position **252**.

The current user position **252** for the digital asset can be included within the usage data associated with the user of the user computing device that is consuming (e.g., playing) the digital asset being represented by the digital asset representation **250**. The usage monitor **214** can track and record the current user position **252**. In addition, the usage monitor **214** can also support one or more trigger points for a given digital asset. The trigger points are positions of a playback or usage of a digital asset. Typically, although not necessarily, the one or more trigger points are provided towards the end of a consumption of the digital asset. For example, a near end marker **254** can be associated with the digital asset. When the current user position **252** exceeds the near end marker **254**, it can be denoted that the usage of the digital asset is nearing

completion. In such cases, the usage monitor **214** can signal the predictive asset manager **208**. The predicted asset manager **208** can then operate to acquire one or more related digital assets that are related to the digital asset being consumed.

The predicted asset manager **218** can cause predicted digital assets to be obtained from a remote media server and stored to a portion of the local data storage **206**. For example, the predicted asset manager **218** can predict (e.g., using a trigger point, such as a near-end marker **254**) that the user will soon desire to acquire information about a related digital asset to the digital asset being consumed. Hence, one or more related digital assets can be obtained from a remote server and downloaded via the network interface **212** to the local data storage **216** where the one or more related digital assets can reside at least temporarily in the event that the user computing device **200** (by user request or programmatic request) attempts to access such digital assets.

Thereafter, by another subsequent trigger point, by programmatic request or by user request, the central controller **202** can, for example, cause customized information to be presented to the user by way of the output device **208**. For example, the output device **208** can present information about other digital assets that are related to the digital asset being consumed. Here, the one or more related digital assets obtained in advance by the predicted asset manager **218** can be accessed from the local data storage **206** by the central controller **202** and presented on the output device **208**.

FIG. 3 is a flow diagram of a data acquisition process **300** according to one embodiment. The data acquisition process **300** can be performed by a user computing device, such as the user computing device **106** illustrated in FIG. 1.

The data acquisition process **300** can monitor **302** usage of a first digital media asset. Here, as the first digital media asset is being consumed at the user computing device, the usage thereof can be monitored **302**. Usage can be evaluated based on the usage data. In one embodiment, the usage is as to a particular digital media asset (e.g., the first digital media asset); however, in other embodiments, usage can be generally applicable to a user or a category of digital assets. The usage monitoring **302** can cause usage data to be stored at the user computing device. Next, a decision **304** can determine whether usage has reached a trigger point. As an example, a trigger point can correspond to a near-end trigger point or an end trigger. When the decision **304** determines that usage has not reached a trigger point, a decision **306** can determine whether the data acquisition process **300** should quit. When the decision **306** determines that the data acquisition process **300** should quit, the data acquisition process **300** can end. Alternatively, when the decision **306** determines that the data acquisition process **300** should not quit, the data acquisition process **300** returns to repeat the block **302** and subsequent blocks so that usage of the first digital media asset can be continuously monitored **302**.

Once the decision **304** determines that usage has reached a trigger point, additional digital media data affiliated with the first digital media asset can be determined **308**. Although the nature of the affiliation can differ depending upon implementation, in one example, the first digital media asset can pertain to an audio e-book and the additional digital media data can pertain to an audio e-book from the same author. As another example, the first digital media asset can pertain to a television show and the additional digital media data can pertain to a subsequent show of the same television series.

After the additional digital media data has been determined **308**, the additional digital media data can be retrieved **310**. For example, the additional digital media data can be

retrieved **310** from a remote media server, such as the online media server **102**. The additional digital media data can then be stored **312** in local storage (e.g., local data storage **206**). Following block **312**, the data acquisition process **300** can return to repeat the block **302** and subsequent blocks so that usage can be monitored and so that appropriate additional digital media data can be determined, retrieved and stored so that it is readily accessible from the local storage at the user computing device.

FIGS. 4A and 4B are flow diagrams of a data retrieval process **400** according to one embodiment. The data retrieval process **400** can, for example, be performed by a user computing device, such as the user computing device **106** illustrated in FIG. 1.

The data retrieval process **400** can monitor **402** usage of a first digital media asset at the user computing device. A decision **404** can determine whether usage of the first digital media asset being monitored **402** has exceeded a near-end mark. A near-end mark is one implementation of a trigger point, where the trigger point is positioned near the end of a digital media asset. For example, a near-end trigger point can be provided at any position of a digital media asset that is prior to its end. Typically, the position of the near-end trigger depends on the particular type of digital media asset and how fast it is (or can be) consumed. In a first example, a user might be progressing slowly through a digital media asset (e.g., audiobook, game), while another user might progress faster through a digital media asset. Here, in the first example, the near-end trigger for the "fast progressor" would perhaps be set further from the end than the near-end trigger for the "slow progressor". In a second example, a digital media asset having of 30 minutes duration can use a trigger point that is farther from its end point as a percentage of its content than would, in one embodiment, be the case for another digital media asset having 3 hours duration.

When the decision **404** determines that usage of the first digital media asset has exceeded the near-end mark, additional digital media data affiliated with the first digital media asset can be determined **406**. The additional digital media data can be retrieved **408** from a remote storage. For example, the remote storage can pertain to any network-accessible data storage device or system. The additional digital media data can be stored **410** in the local data storage of the user computing device.

Thereafter, a decision **412** can determine whether usage of the digital media asset had exceeded an end-mark. When the decision **412** determines that usage has exceeded the end mark, a decision **414** can determine whether additional digital media data is already stored in local storage. When the decision **414** determines that the additional digital media data is stored in local storage, the data retrieval process **400** returns to repeat the block **402** and subsequent blocks. Also, when the decision **412** determines when the usage has not exceeded an end mark, the data retrieval process **400** can also return to repeat the block **402**.

On the other hand, when the additional digital media data is available from local storage, at least a portion of the additional digital media data can be retrieved from the local storage. The retrieved data can then be presented **418**. Here, the retrieved data can pertain to data that was previously predicted to be of interest to the user of the user computing device and thus pre-stored in the user computing device. Hence, the retrieved data can be presented **418** to the user by way of the user computing device, such as by displaying the retrieved data or by playing the retrieved data.

In one implementation, the presentation **418** of the retrieved data can present to the user an opportunity to pur-

chase at least a portion of the retrieved data. In this regard, a decision **420** can determine whether a purchase request with respect to the retrieved data has been received. When the decision **420** determines that a purchase request has been received, purchase of at least a portion of the retrieved data can be initiated **422**. A decision **424** can then determine whether purchase of the at least a portion of the retrieved data has been successful. When the decision **424** determines that the purchase has been successful, the data retrieval process **400** can operate to enable **426** use of the at least a portion of the retrieved data.

On the other hand, when the decision **424** determines that purchase of at least the portion of the retrieved data has not been successful, an error message can be displayed **428**. Typically, the error message would be displayed at the user computing device. Following the block **426** or following the block **428**, and as well as following the decision **420** if a purchase request is not received, a decision **430** can determine whether the data retrieval process **400** should quit. When the decision **430** determines that the data retrieval process **400** should not quit, the data retrieval process **400** can return to repeat the block **402** and subsequent blocks so that the data retrieval process **400** can be continuously performed. However, it should be noted that in other embodiments, the data retrieval process **400** need only be occasionally or less frequently performed. Alternatively, when the decision **430** determines that the data retrieval process **400** should quit, the data retrieval process **400** can end.

Conventionally, searches of digital assets are not performed differently for different users. That is, the search results are the same regardless of the user requesting the search. However, it may be advantageous to provide search results that are customized for particular users, whereby the search results can differ for different users. Hence, according to another aspect, improved search processing can be provided by customizing search results based on characteristics, interests, tendencies or preferences of particular users. In one embodiment, a search of digital assets being requested by a user can be performed in view of usage data associated with the requesting user. For example, results of a search can be ranked in accordance with the usage data. The usage data can result from monitoring usage of an electronic device (e.g., mobile electronic device).

FIG. **5** is a block diagram of a user computing device **500** according to another embodiment. The user computing device **500** includes a central controller **502**. The central controller **502**, for example, can include a central processing unit (CPU). The central controller **502** can include support for data searching, such as searching digital media assets. Namely, the central controller **502** can include or operate to provide a media search module **504**. The media search module **504** can operate to search a repository of digital media assets. The repository of digital media assets can, for example, be a remote media storage server or a local media library at the user computing device **500**.

The user computing device **500** can include a local data storage **506**. The local data storage **506** can store one or more digital assets, such as digital media assets. Those digital media assets stored to the local data storage **506** can be referred to as a local media library.

The media search module **504** can be controlled by the central controller **502** to search through the digital assets stored in the local data storage **206** (i.e., the local media library). The search results from the media search module **504** can be directed by the central controller **502** to an output device **508**. An input device **510**, such as a user input device, can be utilized by the central controller **502** to designate one

or more search criteria to be used by the media search module **504**. The input device **510** can also be used to provide other user inputs to the central controller **502**.

The user computing device **500** can also include a network interface **512**. The network interface **512** can enable the user computing device **500** to interact with online media server via a network, such as the online media server **102** and the network **104** illustrated in FIG. **1**. Consequently, the user computing device **500** can send commands, received responses and/or receive digital assets from the online media server **102**. The digital asset(s) being received from the online media **102** via the network can be stored to the local data storage **206**. Alternatively, the digital asset(s) being received from the online media server **102** can be streamed to an output device **208**. The media search module **504** can be used to search digital assets available from the online media server **102**.

The user computing device **50** can also include a usage monitor **514**. The usage monitor **514** is provided within the user computing device **500** to monitor usage by the user of the user computing device **500**. In doing so, the usage monitor **514** can record usage data **516**. The usage data **516** can be stored with in the usage monitor **514** as shown in FIG. **5**. Alternatively or additionally, the usage data **516** can be stored to the local data storage **506**. The usage data **516** can be acquired and manipulated or updated over time to provide a reliable data set that can be used to assist in customizing search results for the user.

FIG. **6** is a flow diagram of a customized search process **600** according to one embodiment. The customized search process **600** can, for example, be performed by an electronic device, such as the user computing device **106** illustrated in FIG. **1**.

The customized search process **600** can present **602** a search graphical user interface (GUI) on the electronic device. The search GUI enables a user to request a user search. Typically, a user would interact with the search GUI to enter one or more search criteria into one or more user input regions prior to requesting that a search be performed. After the search GUI has been presented **602**, a decision **604** can determine whether a user search request has been received at electronic device. When the decision **604** determines that a user search request has not been received, a decision **606** can determine whether the customized search process **600** should quit. When the decision **606** determines that the customized search process **600** should quit, the customized search process **600** can end. Alternatively, when the decision **606** determines that the customized search process **600** should not quit, then the customized search process **600** returns to repeat the block **602** and subsequent blocks so that the user has the ability to interact with the search GUI to provide a user search request.

Once the decision **604** determines that a user search request has been received, usage data pertaining to the electronic device or its user can be accessed **608**. Next, a search for digital media assets that match the user search request can be initiated **610**. After a search has been initiated **610**, a decision **612** can determine whether search results have been received. When the decision **612** determines that search results have not yet been received, the customized search process **600** can await such search results.

On the other hand, when the decision **612** determines that search results have been received, the search results can be ranked **614** based in part on the usage data. The usage data can, upon evaluation, suggest content that is more likely to be of interest to the user of the electronic device. Hence, these search results can be ranked **614** such that those of the digital assets within the search results that are more likely to be of

11

interest to the user (e.g., based on the usage data) can be ranked higher than other digital assets within the search results. Thereafter, the ranked search results can be presented **616**. For example, the ranked search results can be displayed on a display device associated with the electronic device. After the ranked search results have been presented **616**, the customized search process **600** can end. However, in some embodiments, prior to ending the customized search process **600**, additional processing could be performed to present additional ones of the ranked search results, to preview one or more of the digital assets within the ranked search results, and/or to purchase one or more of the digital assets within the ranked search results.

In the customized search process **600**, the search results can be ranked **614** at the electronic device (e.g., user computing device **106**) after the search results are received. Alternatively, the search and the ranking can be performed by a remote server prior to returning the search results to the electronic device.

Another aspect of the invention is a search graphical user interface (GUI). The search GUI can facilitate a user requesting a search and/or presenting results of a search to the user. FIGS. 7A-7D illustrate exemplary search screens of a search GUI according to one embodiment. The search GUI can be displayed on a display device associated with an electronic device.

FIG. 7A is an illustration of a search GUI **700** according to one embodiment. The search GUI **700** can include a search box **702** capable of receiving a search text string that has been input by a user. The search GUI **700** also includes a facet region **704** that includes one or more user-selectable facets that can impact a search to be performed. As illustrated in FIG. 7A, the facet region **704** can include a category facet **706**, a release date facet **708**, a star rating facet **710**, a price facet **712**, and a type facet **714**. Besides these illustrated facets, other facets can be additionally or alternatively utilized depending upon the particular implementation. Also, in the case of the category facet **706**, it should also be noted that an additional facet could pertain to a sub-category. For each of the facets **706-714**, on selection, a list or menu of available items can be presented. A user can select one of the available items associated with each of the facets. For example, the category facet **706** can include a list of selectable categories. Examples of categories for mobile device software applications can include: all, books, business, education, entertainment, finance, games, healthcare & fitness, lifestyle, medical, music and navigation. The star rating facet **710** can provide a list of selectable ratings. Examples of ratings can include: all, 5 star, 4 star, 3 star and 2 star. The type facet **714** can provide a list of selectable types of electronic devices for which the digital assets are to be usable on. Examples of types can include: all, netbook (e.g., iPad™) and smart phone (e.g., iPhone™).

The facet region **704** can also include a reset facet **716**. Upon user selection of the recent facet **716**, all the facets **706-714** can all reset to their default state, as illustrated in FIG. 7A.

Still further, the search GUI **700** can also include a results region **718**. Here, the results of a search that has been performed in accordance with a search text string provided in the search text string box **702** as well as in accordance with the plurality of facets within the facet region **704**. The results of the search can be presented in the results region **718** in a variety of different ways. For example, the results of the search can be presented as a list of matching digital assets, namely digital media assets. As discussed above, the results of the search can be ranked in accordance with usage data.

12

However, as illustrated, since the search text string box **702** is empty, no search has been performed and thus the results region **718** is empty.

FIG. 7B is an illustration of a search GUI **700'** according to one embodiment. The search GUI **700'** represents the search GUI **700** illustrated in FIG. 7A in which the results region **718** is now represented as the results region **718'**. Here, representative search results are depicted in the results region **718'**. As an example, the results region **718'** illustrated in FIG. 7B illustrates four (4) distinct digital media assets **720** being concurrently represented. These four distinct digital media assets **720** are all or part of a set of digital media assets that are the search results. In this illustrated embodiment, for each of the digital media assets **720**, the representation can, for example, include a graphic **722**, descriptive information **724**, a price **726** and a "buy" button **728**. The graphic **722** can pertain to an image associated with the digital media asset **720**. For example, the image can pertain to a representative image (e.g., an album cover or a poster), a corporate logo, and the like. The descriptive information can, for example, provide artist or developer name, category, date released or updated, and/or rating information. The rating information can, for example, include a rating as well as a number of ratings that form the basis for the rating.

FIG. 7C is an illustration of a search GUI **700"** according to one embodiment. The search GUI **700"** represents the search GUI **700** illustrated in FIG. 7A in which a specific search has been requested. In this example, the search key word "graphics" **730** has been entered into the search box **702**. The plurality of facets within the facet region **704'** remain in their default settings. The results of the search are partially presented in the results region **718"**. Each of the digital media assets **720** that match the keyword **730** as well as the facet settings can be presented similar to that discussed above in FIG. 7B. Additionally, the facet region **704'** includes a numerical reference **732** and a sort control **734**. The numerical indicators **732** can specify the number of digital media assets that match the search criteria. In addition, the numerical indicators **732** can also indicate those of the set of digital media assets that match the search criteria are being presented. For example, as shown in FIG. 7C, and the numerical indicator specifies "1-4 of 1000", meaning that the first four of the matching digital media assets are presented in the results region **718"**. The sort control **734** is a user selectable control and that enables a user to sort the matching digital media assets within the results region **718"**. By sorting the matching digital media assets, the order in which the various digital media assets are presented can be controlled.

FIG. 7D is an illustration of a search GUI **700'''** according to one embodiment. The search GUI **700'''** represents a modification to the GUI **700"** illustrated in FIG. 7C. Specifically, several of the facets within the facet region **704"** have been user selected so as to specify different search criteria than the default criteria. Specifically, the category facet **706** has been selected to the category "Games", and the release date facet **708** has been selected to limit the release date to "This Month", and the star rating facet **710** has been selected to limit the search results to those digital media assets having a star rating of at least "5 stars". It should also be noted that the numerical indicator **732'** is also updated to reflect that the number of matching digital media assets has now been reduced to **210** through use of the search criteria imposed by the facets **706**, **708** and **710** which serves to further limit the scope of the search. The digital media assets **720** being depicted in the results region **718'''** are not necessarily the same digital media assets being presented in the results region **718"** shown in FIG. 7C.

## 13

Although the facets **706-714** discussed above in FIGS. 7A-7D are user-selected, in another embodiment, one or more of the facets **706-714** can be automatically selected based on usage data. In such an embodiment, a user could allow the electronic device to determine the facet settings based on usage data. As discussed above, usage data can be monitored and then used for customization. Here, the usage data can be used to automatically set one or more of the facet settings. The search GUI could, as an example, not present the facets **706-714** for user selection if the facets were automatically selected. However, even if the facets are automatically determined by the electronic device, a user may still desire that the facets **706-714** be displayed so as to be able to over-ride or set one or more of the facets.

The various aspects, features, embodiments or implementations of the invention described above can be used alone or in various combinations.

Embodiments of the invention can, for example, be implemented by software, hardware, or a combination of hardware and software. Embodiments of the invention can also be embodied as computer readable code on a computer readable medium. The computer readable medium is any data storage device that can store data which can thereafter be read by a computer system. Examples of the computer readable medium generally include read-only memory and random-access memory. More specific examples of computer readable medium are tangible and include Flash memory, EEPROM memory, memory card, CD-ROM, DVD, hard drive, magnetic tape, and optical data storage device. The computer readable medium can also be distributed over network-coupled computer systems so that the computer readable code is stored and executed in a distributed fashion.

Numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will become obvious to those skilled in the art that the invention may be practiced without these specific details. The description and representation herein are the common meanings used by those experienced or skilled in the art to most effectively convey the substance of their work to others skilled in the art. In other instances, well-known methods, procedures, components, and circuitry have not been described in detail to avoid unnecessarily obscuring aspects of the present invention.

In the foregoing description, reference to "one embodiment" or "an embodiment" means that a particular feature, structure, or characteristic described in connection with the embodiment can be included in at least one embodiment of the invention. The appearances of the phrase "in one embodiment" in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments mutually exclusive of other embodiments. Further, the order of blocks in process flowcharts or diagrams representing one or more embodiments of the invention do not inherently indicate any particular order nor imply any limitations in the invention.

The many features and advantages of the present invention are apparent from the written description. Further, since numerous modifications and changes will readily occur to those skilled in the art, the invention should not be limited to the exact construction and operation as illustrated and described. Hence, all suitable modifications and equivalents may be resorted to as falling within the scope of the invention.

What is claimed is:

1. A method for processing a search request, the method comprising:

receiving a search request from an electronic device, the search request including one or more search criteria;

## 14

searching a database in accordance with the one or more search criteria to obtain search results, the database including digital asset information pertaining to a plurality of digital media assets and the search results corresponding to different digital media assets;

monitoring usage of the electronic device to determine usage data, wherein monitoring the usage includes determining a level of completion of a digital media asset consumed by the electronic device;

determining, based on the level of completion of the digital media asset consumed by the electronic device, that a particular type of digital media asset is of more interest to a user of the electronic device compared to another type of digital media asset when the level of completion of the digital media asset consumed by the electronic device has exceeded a trigger point of the digital media asset, wherein the trigger point indicates a position in the digital media asset;

ranking the search results based at least in part on the usage data and the particular type of digital media asset determined to be of more interest to the user compared to the other type of digital media asset, wherein ranking the search results includes increasing a ranking for digital media assets belonging to the determined particular type of digital media assets compared to digital media assets of the other type within the search results; and

presenting the ranked search results via the electronic device.

2. The method of claim 1, wherein the search results includes resultant digital asset information pertaining to a subset of the plurality of digital media assets.

3. The method of claim 1, wherein the usage data pertains to historical usage of the electronic device or its user.

4. The method of claim 1, wherein the searching is influenced by the usage data.

5. The method of claim 1, wherein the one or more search criteria comprises one or more search facets that further limit a scope of the search, and wherein presenting the ranked search results comprises displaying information concerning a set of the digital media assets that fall under the one or more search facets.

6. The method of claim 5, wherein the one or more search facets are automatically determined by the electronic device.

7. The method of claim 5, wherein the one or more search facets are each individually user-selectable.

8. The method of claim 1, further comprising:

enabling purchase of at least a portion of the ranked search results;

determining whether a purchase request with respect to the ranked search results has been received; and

purchasing at least the portion of the ranked search results when the purchase request has been determined to be received.

9. The method of claim 1, wherein a category of a digital media asset is one of a group consisting of a television show, a musical piece, a video, an electronic book, an audiobook, a software game, and a podcast.

10. The method of claim 1, wherein searching the database includes searching digital media assets resident at a local repository of the electronic device and digital media assets resident at a remote repository associated with an online media server.

11. The method of claim 1, wherein the position of the trigger point in the digital media asset is dependent upon the particular type of the digital media asset and duration of the digital media asset.

15

12. The method of claim 1, wherein different types of digital media assets have trigger points in different positions of the digital media assets.

13. The method of claim 1, wherein the plurality of digital media assets corresponds to a plurality of mobile device software applications, wherein the plurality of mobile device software applications includes at least one of a book application, a business application, an education application, an entertainment application, a finance application, a game application, a healthcare and fitness application, a lifestyle application, a medical application, a music application, or a navigation application.

14. The method of claim 1, wherein presenting the ranked search results includes presenting a representation of a software application, descriptive information for the software application, and a price to acquire the software application.

15. A computer readable memory encoded with a set of program instructions that, when executed, causes a processor to execute a method, the method comprising:

receiving a search request from an electronic device, the search request including one or more search criteria;

searching a database in accordance with the one or more search criteria to obtain search results, the database including digital asset information pertaining to a plurality of digital media assets and the search results corresponding to different digital media assets;

monitoring usage of the electronic device to determine usage data, wherein monitoring the usage includes determining a level of completion of a digital media asset consumed by the electronic device;

determining, based on the level of completion of the digital media asset consumed by the electronic device, that a particular type of digital media asset is of more interest to a user of the electronic device compared to another type of digital media asset when the level of completion of the digital media asset consumed by the electronic

16

device has exceeded a trigger point of the digital media asset, wherein the trigger point indicates a position in the digital media asset;

ranking the search results based at least in part on the usage data and the particular type of digital media asset determined to be of more interest to the user compared to the other type of digital media asset, wherein ranking the search results includes increasing a ranking for digital media assets belonging to the determined particular type of digital media assets compared to digital media assets of the other type within the search results; and presenting the ranked search results via the electronic device.

16. The computer readable storage medium of claim 15, wherein the search results includes resultant digital asset information pertaining to a subset of the plurality of digital media assets.

17. The computer readable storage medium of claim 15, wherein the one or more search criteria are determined automatically based on the usage data.

18. The computer readable storage medium of claim 15, wherein the method further comprises:

receiving a user selection for at least one of the one or more search criteria.

19. The computer readable storage medium of claim 15, wherein presenting the search results comprises displaying information concerning a set of the digital media assets that match at least the one or more search criteria.

20. The computer readable storage medium of claim 15, wherein the one or more search criteria are presented as user interface elements on a display device associated with the electronic device, and wherein the user interface elements are user-selectable.

21. The computer readable storage medium of claim 15, wherein at least one of the user interface elements enable selection of one of a list of selectable search criteria.

\* \* \* \* \*